WITH HEMMED EDGE -GALVANIZED ANGULAR SHANK ROOFING NAILS 4" (102 mm) O.C. STAGGERED OR EVERGUARD® TPO UTILITY FLASHING MEMBRANE (TPO DRILL-TEC[™] FASTENERS 12" (305 mm) O.C. -REINFORCED EVERGUARD® MEMBRANE ONLY) OR MIN. 8" (203 mm) WIDE REINFORCED (PERIMETER SHEET IF REQUIRED) EVERGUARD® MEMBRANE MULTIPLE LAYERS OF ENERGYGUARD™ ROOF INSULATION -ROOF DECK/SUBSTRATE - WOOD NAILER, 5/4" (31.8 mm) x METAL FASCIA CLEAT 4" (102 mm) MIN. SECURED TO FASTENED WITH DRILL-TEC™ DECK FASTENERS 12" (305 mm) O.C. SHEET METAL **GUTTER BY OTHERS**

GUTTER WITH COATED METAL EDGE DETAIL

Scale: N.T.S.



- 1. REFER TO EVERGUA ® DETAIL 204 FOR COATED METAL JOINTS.
- 2. A CONTINUOUS METAL CLEAT IS REQUIRE
- 3. 25-YEAR GUARANTEES AND ABOVE MUST USE EXTREME ACCESSORIE
- 4. FOR HEAT-WELDING LAPS USE 1.5" (38.1 mm) WELD WITH MACHINE AUTOMATIC WELDER AND 2" (50.8 mm) WELD WITH HA WELDER.





Notes: This detail is in accordance with the BRANZ Appraisal and CodeMark certification. Please contact us for any required customization.

© Ultraguard LTD

Technical Support and Advice: Email: technical@gaf.nz

Call: 0800 42 33 55

Web: www.gafroofing.co.nz/TPO
GAF New Zealand Distributor

Drawing Title:

GAF EverGuard TPO Roofing

EVERGUARD® COATED METAL DRIP EDGE

REF:

Version:

Α

T-901 17/01/2025

Date: