


FRONT SIDE OF
PARAPET WALL

FASTEN SCUPPER MEMBRANE ON FRONT SIDE OF PARAPET WALL
WITH EVERGUARD® TERMINATION BAR (OPTIONAL)



REFER TO
PARAPET WALL
AND CURB DETAIL
FOR TERMINATION

EVERGUARD®
COATED METAL
WITH HEMMED
EDGE

DRILL-TEC™ PLATES & FASTENERS 12" (305 mm) O.C.
(6" [152 mm] O.C. FOR BALLASTED SYSTEMS)

PREMANUFACTURED OR UNREINFORCED FIELD
FABRICATED CORNERS
- HEAT WELDE

REINFORCED EVERGUARD®
MEMBRANE

MULTIPLE LAYERS OF
ENERGYGUARD™ ROOF
INSULATION

ROOF DECK/SUBSTRATE

WOOD NAILER, 2" (50.8 mm) x 4" (102 mm) MIN.
WIDE SECURED TO DECK (OPTIONAL)

SCUPPER - FIELD FABRICATED OPEN TOP - OVERFLOW

Scale: N.T.S.

NOTE:

1. . DETAIL TO BE USED IN CONJUNCTION WITH STANDARD GUIDE SPECIFICATION CONTAINING REQUIREMENTS FOR NAILER INSULATION ETC.
2. . FOR INSULATION THICKNESS GREATER THAN 8" (203 mm), A COVER BOARD IS REQUIRED ON MECHANICALLY ATTACH SYSTEMS ONLY.
3. . IF EVERGUARD® FREEDOM™ MEMBRANE IS USED, BONDING ADHESIVE IS NOT NEEDED AND WALL MUST BE PRIMED.



Notes: This detail is in accordance with the
BRANZ Appraisal and CodeMark certification.
Please contact us for any required customization.
© Ultraguard LTD

Technical Support and Advice:
Email: technical@gaf.nz
Call: 0800 42 33 55
Web: www.gafroofing.co.nz/TPO
GAF New Zealand Distributor

Drawing Title:
GAF EverGuard TPO Roofing

REF:
T-921

Date:
17/01/2025

Version:
A